POSIFLEX



GEN9 Base

Highly integrated POS Terminal base stand with its own power distribution. Support a wide range of POS terminals (ZT , RT, XT and PS Series. Elegant and compact design, All-In-one retail solution.

Specification	
Dimension (W x D x H in mm)	274 x 274 x 373 (system or second display not included)
Environmental	
Operating Condition	0°C - 40°C , 20%RH - 90%RH
Storage Condition	-20°C - 70°C , 10%RH - 90%RH
Power	
Power Source	Built-in 24V/120W power adapter
Power Board	1 x 24V DC-IN connector (for built-in power adapter only) 2 x 24V DC-OUT connector 2 x 12V DC-OUT connector
System Support	
VESA 75x75	Provided as accessories, for RT and ZT series terminal
VESA 100x100	Default, for XT and PS series terminal
Attachment Options	
Second Monitor	Non-touch TFT LCD: 15"(LM-5015), 15.6"(LM-5016) PCAP touch TFT LCD: 15"(TM-5015), 15.6"(TM-5016)
Thermal Printer	PP-7900, 3" thermal printer w/auto cutter, 250 mm/sec (max.); Tray for EPSON TM-M30 III/M50/M55

e-Merchant

บริษัท อี-เมอร์แชนท์ จำกัด 7/129 เซ็นทรัลทาวเวอร์ ปีนเกล้า ชั้น 17 ถนนบรมราชชนนี แขวงอรุณอมรินทร์ เขตบางกอกน้อย กรุงเทพฯ 10700

โทรศัพท์ 02-026-6299 โทรสาร 02-884-9166 Website : http://www.e-merchant.co.th