KEPLER
GX-1560i3



Specification	GX-1560i3
CPU	Intel® Kaby lake - U Processor : i3-7100U (2 core 4 thread, up to 2.4 GHz , 15Watt)
Chipset	Intel® HD Graphics 620
System Memory	DIMM DDR3 x 1, 8GB
Thermal Solution	Fan - Free
OS	Windows 10 IoT

Display

LCD Size	15" TFT LCD Panel (LED Backlight)
Resolution	1024 x 768
Touch Screen	Muti Capacitive Touch Screen

Storage Device

HDD/SSD	SSD mSATA 512GB

I/O Ports

Serial Port	1x DB9 Port
Parallel Port	1x Built-in LPT
USB	2 x 3.0 Port 2 x 2.0 Port
Ethernet Port	1 x Gigabit Ethernet 10/100/1000 Mbps
Display Port	1 x VGA 1 x HDMI
Speaker	1x Internal 2W Speaker

Communication

Wifi	Support Extension Wifi / Bluetooth / 3G / 4G

Others

Operation environment	Temperature : 0~50°C ; Humidity : 10~80%
Color Select	Black
Material	Plastic / Aluminuim

Additional Option

2nd Display	10.1 inch 16:9 Industrial grade panel without Touch 350 nits, 30K hours LED backlight
VFD	40 characters (20 columns x 2 lines) Character Size : 9.03*5.25 mm Brightness : 500 cd/m
MSR	Swiping speed : 3 ipds to 60idps (7 cm/s to 150 cm/s)

e-Merchant Co., Ltd.
Tel : 02-026-6299
Exclusive Member

@emc.partner
emerchant.th

17th Floor, Central Tower Pinklao, 7/129
Baromrajchonnee Rd., Arun Amarin,
Bangkok-noi, Bangkok 10700, Thailand

http://www.e-merchant.co.th